

Ozone

Ozone offers a new dimension to the ANN SACKS® porcelain assortment. Truly a best-in-class metallic porcelain flooring product, Ozone is produced with an unsurpassed attention to detail. The color and finish quality are superb. The palette is rich and timeless. The surface finish utilizes a random machined effect that enhances overtime. Chrome and Silver coordinate beautifully with our Mirror wall tile for a dramatic modern installation.



RECOMMENDED USE

- Suitable for indoor wall and moderate duty flooring applications (note exceptions)
- Not recommended for outdoor use as elements may affect finish
- Not recommended for wet areas such as pools or fountains as chemicals may cause discoloration
- Caution recommended for kitchen or bathroom areas as finish may be susceptible to oil staining and may etch where acidic substances or cleaners are frequently used, particularly hydrochloric acid.
- Testing data available upon request
- Please see Ann Sacks slip resistance and wet flooring application statement to determine usage in a wet area



floor



high-traffic



wall



shower wall

INSTALLATION AND MAINTENANCE

- Please reference the TCNA handbook for installation of ceramic tile (www.tcnatile.com)
- It is recommended to seal tile before and after grouting to provide stain protection as this product may be affected by construction tape, silicone or other construction materials
- Non-sanded grout recommended
- Do not use epoxy or latex modified grouts as the additives may stain the tile

COLLECTION

Field	11¾" x 23½" <i>*Limited Quantity Available in certain formats, Please check with your sales associate</i>
Material	Porcelain
Color	Silver
Lead Time	Typical Lead Times are 1-2 weeks <i>(Lead Times are subject to change)</i>



Silver




*Please note: variations in color, shade, surface texture and size are natural characteristics of all our products and should be expected. Images shown are representative, but may not indicate all variations in these characteristics.

10/2017

ANN SACKS.

www.annsacks.com | 1.800.278.8453

Collection

Product	Description	Colors Available	Size	Weight/Pc.
<div>FIELD</div> <div><div>23 1/2"</div><div>11 3/4"</div></div>	Ozone 11 3/4" x 23 1/2"	Chrome, Silver	11.713 X 23.445 x 0.375	8.492
<div>TRIM</div> <div><div>2 7/8"</div><div>23 1/2"</div></div> <div><div>Profile</div></div>	Ozone 2 7/8" x 23 1/2"	Chrome, Silver	2.874 X 23.445 X 0.375	2.156

*Please note: variations in color, shade, surface texture and size are natural characteristics of all our products and should be expected. Images shown are representative, but may not indicate all variations in these characteristics.

Technical Characteristics

Breakage Resistance EN ISO 10545-4 61 N/mm ²	Surface Hardness EN 101 MOHS 5	Anti-Slip Resistance DIN 51130 N/A (Not Tested)	Stain Resistance EN ISO 10545-14 Visible Defects
Deep Abrasion Resistance ISO 10545-6 141 mm ³	Resistance To Chemical Etching EN ISO 10545-13 Average	Water Absorption EN ISO 10545-3 +/-0.1%	Frost Resistance ISO 10545-12 Anti-Ice

*Please note: variations in color, shade, surface texture and size are natural characteristics of all our products and should be expected. Images shown are representative, but may not indicate all variations in these characteristics.

06/04/2014



Ozone offers a new dimension to the ANN SACKS® porcelain assortment. Truly a best-in-class metallic porcelain flooring product, Ozone is produced with an unsurpassed attention to detail. The color and finish quality are superb. The palette is rich and timeless. The surface finish utilizes a random machined effect that enhances overtime. Chrome and Silver coordinate beautifully with our Mirror wall tile for a dramatic modern installation.

Product Usage Recommendations

- Suitable for indoor wall and moderate duty flooring applications. (note exceptions)
- Complies with ADA slip requirements for horizontal surfaces in wet environments.
- Not recommended for outdoor use as elements may affect finish.
- Not recommended for wet areas such as pools or fountains as chemicals may cause discoloration.
- Caution recommended for kitchen or bathroom areas as finish may be susceptible to oil staining and may etch where acidic substances or cleaners are frequently used, particularly hydrochloric acid.
- Testing data available upon request.

Installation & Maintenance Guidelines

- Install per industry standards for porcelain tile.
- Always inspect material prior to installation; installed material cannot be accepted for return or credit.
- It is recommended to seal tile before and after grouting to provide stain protection as this product may be affected by construction tape, silicone, or other construction materials.
- Non-sanded grout recommended.
- Do not use epoxy or latex modified grouts as the additives may stain the tile.

Description

Field : 11 ³/₄" x 23 ¹/₂"

Trim : 2 ⁷/₈" x 23 ¹/₂" surface bullnose

